

# Brifen Wire Rope Barrier

Experience the unparalleled safety and reliability of the Brifen Wire Rope Barrier, the definitive solution in road safety barriers. Instantly recognisable by its unique weave pattern, this safety system provides protection, confidently meeting NCHRP 350 TL3 and TL4 standards. Its innovative design enables tighter radius installations, ensuring optimal performance in all road conditions. With rigorous testing to AS/NZS3845:1999 / NCHRP 350 standards, the system is engineered to withstand dynamic impacts, including those from an 820kg compact vehicle at 100km/hr and an 8000kg single unit van truck at 80km/hr.



# Brifen Wire Rope Barrier

Easy to install and low supply cost with fast repair options



## FEATURES

- Meets AS/NZS3845:1999 and NCHRP 350
- Low supply and installation cost
- Easy installation and repair
- Speedy repair
- Unique weave pattern and tight radius
- Suitable for steep sag and floodways
- Will suit bridge and culvert applications

## SPECIFICATIONS

### CONTAINMENT LEVELS

MASH TL3	Designed for a 2270kg pick-up truck at 100km/h
MASH TL2	Designed for a 2270kg pick-up truck at 70km/h.

### SYSTEM SPECIFICATIONS

System Length	6.93m (TL3) 4.33m (TL2)
System Height	830mm (TL3 and TL2)
System Width	877mm (TL3 and TL2)
Max Hazard Width	762mm (TL3 and TL2)
System Mass	1135kg (TL3) 770kg (TL2)

### CONSTRUCTION AND INSTALLATION

System Finish	Hot dip galvanised for durability
Ground Surface	Suitable for concrete or asphalt
Number of Anchor	25 off M20 for concrete 53 off M20 for asphalt

For more information and specialist advice contact your Account Manager or local branch hub on 134040.

