

## Zoneguard Barrier™

Enhance safety on your construction sites and highways with our innovative Zoneguard™ steel barrier. This proprietary portable longitudinal barrier is uniquely designed to provide superior protection for drivers as well as road and construction crews. This barrier provides contractors with both TL-3 and TL-4 deployment options and anti-gawk screens for further safety improvements on major roadworks sites.



# Zoneguard Barrier™

Cost effective and efficient protective barriers



## FEATURES

- **Versatile Use:** Zoneguard™ provides contractors 12m units and 4m units to offer an ultimate solution for freeway and highway applications with several anchoring options to allow contractors to optimise working widths and barrier installation to suit their specific needs.
- **Low Deflection:** Zoneguard™ when installed using close anchoring spacings of 6m (minimum deflection) provides contractors with 0.10m in deflection TL-3 making this an ideal barrier for any site with lateral space constraints across the major road network in Australia.
- **Fully tested and certified** to MASH specifications.

## SPECIFICATIONS

Length	11.85m and 3.95m
Width	700mm
Height	820mm
Weight	1120kg and 375kg
Min. Radius	200m and 7m
Tested and approved minimum deflection	Yes
Material	4mm galvanised steel

Tested to	MASH TL-3 and TL-4
Durable	Yes
Fast Deployment/Retrieval	Yes
Anchoring Required	Yes
Minimum Installation Exposure Time	Yes
Rapid lane switching	Yes

**Note Angle pieces available (subject to site specific assessment and approval).**

	TL-3 Low Deflection	TL-3 Min. Deflection	TL-4 Low Deflection
Test Speed	100km/hm	100km/h	100km/h TL-3 90km/h TL-4
Min. Length	75m	95m	75m
Dynamic Deflection	1.9m	0.10m	2.79m
Working Width	2.6m	0.8m	3.49m
Anchoring	Every 65m (2)	Every 6m (2)	Every 65m (2)
Screens	No	Safe Screen	No

**Note there are options for alternate anchoring solutions with shorter ground penetration (subject to site specific risk assessment).**

**For more information and specialist advice contact your Account Manager or local branch hub on 134040.**

